

# SOLIDE+CLICK

HYBRID WOOD FLOORING

The lightest and strongest hybrid wood flooring

A disruptive solution that embeds NOXGENESIS technology, unique EMT™ Core technology and proven NOX Click'n go and Drop'n go!™ click system

## NOXGENESIS

ADVANCED HYBRID FLOORING TECHNOLOGY

NOXGENESIS is a patent pending technology that NOX invented to create the new standard in hybrid LVT flooring.

This technology is the perfect solution with **high impact resistance**, **increased stability**, **superior profile strength** and **waterproof function**, while being lightweight.

# SOLIDE+CLICK

HYBRID WOOD FLOORING

## Technical Features:

- **More stable:** Superior long-term dimensional stability with EMT™ Core technology of 6 layers
- **More durable:** Stronger durability (much less brittle, higher compression strength)
- **Easier to install:** Easier, stronger and hassle-free installation with proven NOX Click'n go and Drop'n go!™ click system
- **No floor undulation caused by uneven surface imperfections**
- **More diverse designs:** NOX's own 4,000+ designs, 50 authentic embosses and unique 'Built-In-Grout' click system
- **Silent and soft floor:** Silent and softer underfoot feel
- **Superior moisture resistance**
- **More eco-friendly:** Low VOCs and non-phthalate

## Comparison:

Eliminated the drawbacks of WPC	Eliminated the drawbacks of Rigid Core
<ul style="list-style-type: none"> <li>• Better stability against temperature changes up to 176 degrees (80°C)</li> <li>• Better impact resistance over 1,500 PSI compared to 250 PSI with WPC</li> <li>• Superior profile strength, eliminating the brittle profiles that are inherent to WPC</li> </ul>	<ul style="list-style-type: none"> <li>• Better flexibility and performance than stiff rigid core product (SPC) : elimination of "trampoline effect" with unlevelled subfloors</li> <li>• A fraction of the weight (about 40% lighter than regular rigid board / SPC), reducing freight costs</li> <li>• Better softness than rigid core product / SPC</li> </ul>

## Technical Specification:

<b>Thickness</b>	<ul style="list-style-type: none"> <li>• Total thickness: 5mm / 6mm / 8mm with 1mm SOUNDPROTEC backing</li> <li>• Wear-layer option: 0.1 ~1mm (4-40 mil)</li> </ul>
<b>Dimension</b>	185 X 1,212mm, 235 X 1,505mm, 305 X 610mm, 462 X 924mm
<b>Installation Type</b>	Click

## Certified



### Seoul Design Center & Office

KD Center, 355, Hyoryeong-ro,  
Seocho-gu, Seoul, 06643 Korea

Tel +82-2-520-7600  
Fax +82-2-598-9674

### NOX Corp. | KOREA

Shinho Factory  
Shinho 2nd Factory, Yedang  
Enbo Factory  
Godeok Factory  
Bongsan Factory  
Deoksan Factory  
Choongnam, Korea

### NOX US | USA

NOX US  
P.O. Box 824  
931 S. Springville Avenue  
Fostoria, OH 44830  
Office (419) 701-5060  
Fax (419) 701-5058

[www.noxglobal.com](http://www.noxglobal.com)  
[www.noxus.com](http://www.noxus.com)

E-Mail [info@noxglobal.com](mailto:info@noxglobal.com)



✉ [ventas@gecko.com.pe](mailto:ventas@gecko.com.pe)

☎ +511 299 8619 / +511 299 8620

Av. La Encalada 569 Of. 201 A. Surco, Lima - Perú